











الصفحة الرئيسية

المعامل

الخدمات

الملفات

الأبحاث

المواد

## تفاصيل البحث:

Stresses in cross-ply laminated circular cylinders of axially: variable thickness

Stresses in cross-ply laminated circular cylinders of axially variable thickness

This paper presents the results from an analytical: investigation of the behavior of composite circular cylinders subjected to internal and external surface loading. The present cylinder consists of a number of homogeneous ply groups of axially variable thickness. Each ply group forming a layer is treated as an individual thin elastic cylinder of generally orthotropic material with interfacial stresses on the inner and outer surfaces of the layer as boundary loading. The deformation and stresses in each layer can be expressed in terms of interfacial stresses along the exterior surfaces of each layer. All displacement and stresses throughout the composite cylinder can be determined subsequently after satisfying boundary conditions at the inside and outside surfaces of the cylinder in conjunction with the recurrence relationship among interfacial stresses. Numerical results are presented for different values of the inner-to-outer ratio, number of layers, stacking sequence, axially-variablethickness parameter, and load factor. Based on the presented results, conclusions can be drawn concerning the cylinder behavior and its sensitivity to different parameter variations

> : مقال نوع البحث سنة البحث 2006:

الثاشر ACTA MECHANICA Volume: 187 Issue: 1-4 Pages: 85-102:

> Tuesday, June 17, 2008: تاريخ الإضافة على الموقع

نوع الباحث المرتبة العلمية البريد الالكتروني اسم الباحث (انجليزي) اسم الباحث (عربي) أستاذ أشرف مبارز زنقور Zenkour, A. M zenkour@kau.edu.sa

عنوان البحث

الوصف

عمادة الكلبة وكالات الكلبة إدارة الكلية الشؤون التعليمية الأقسام العلمية مجلة كلية العلوم الأنظمة الإلكترونية(ODUS) اتصل بالكلية دليل المنسوبين مواقع مفضلة

عدد زيارات هذه الصفحة: 9



